



## Forsyth County Purchasing Department

---

July 2, 2010

### **Addendum #1 Bin Stocking for the Fleet Department and the Fire Motor Maintenance**

This addendum supersedes and supplements all portions of the bidding documents and becomes part of the contract documents for the above referenced project.

Where any item called for in the specifications or indicated on the drawings is supplemented hereby, the original requirements shall remain in effect

Where any original item is amended, voided or superceded hereby, the provision of such item not so specifically amended, voided or superceded shall remain in effect.

#### **Clarifications:**

- 1) *Please see attached for the list of items for bidding. These are estimated only as high usage items. This list will not bind or limit Forsyth County to these items only.*
- 2) *When submitting quote please list percentage off catalog price and not list price. Bidder must submit two (2) catalogs with sealed bid.*
- 3) *Bid closing date will change to due by 2pm on Thursday, July 22<sup>nd</sup>, 2010.*

No other questions will be accepted.

Stephanie Elrod  
Procurement Agent I  
Forsyth County Purchasing Dept.  
118 Castleberry Rd  
Suite 13  
Cumming, GA 30040  
770-888-8872 (phone)/ 770-205-4666 (fax)



Parts List from Fire Dept Motor Maintenance

Item #	Description	Unit Price
	Grade 8 Bolts USS, Chromium Molybdenum Alloy Steel, Proof load 120,000psi, Minimum Tensile Strength 150,000psi, Typical Strength 160,000psi, Yield Strength 130,000psi, and Hardness 33-39 RC	
1	1/4" - 20 x 1/2"	
2	1/4" - 20 x 3/4"	
3	1/4" - 20 x 1"	
4	1/4" - 20 x 1 1/2"	
5	1/4" - 20 x 1 3/4"	
	Grade 8 High Strength Regular Profile Nuts, Hardness 24-32 RC (1/4 to 5/8) nut size, minimum proof load 150,000, approval SAE J995	
6	1/4" Nut USS Grade 8	
	Extra Heavy-Duty Split Lock Washers, Hardness 38-46 RC, Approval SAE J488	
7	1/4" Split Lock Washer	
	Hardened Flat Washers, Hardness 38-45 RC, Approval SAE J488	
8	1/4" Hardened Flat Washers	
	Solderless Terminals Butt Connectors, Electrolytic Copper/Tin Plating, Rating 600 v max (signs and fixtures), 1000 v max (luminaires), Temp Rating 221 degress F/ 105 degress C, MIL-T-7928,	
9	Gauge size-22-18 red	
10	Gauge size-16-14 blue	
11	Gauge size-12-10 yellow	
	Shrinkable Tubing in Dispenser Box, 25' length, Temp Range 67 degress F to 275 degress F, Dielectric Strenght 500 v/ Mil, Tensile Strength 2000psi, MIL-1-23053-B, Shrink Ratio 2:1	

Item #	Description	DIA. ID BEFORE SHINK MIN	DIA. AFTER SHINK MAX.	Wall Thickness After Shink Max	Unit Price
12	SIZE/WIRE 5/16" and 12-8ga	0.312	0.156	0.025	
13	1/2" and 2-8ga  Poly Split Loom, Temp Range 40 degrees F to 185 degress F/ -40 degrees C to 85 degrees C, Tensile Strength 2000-2400psi, in the color Black CV Resistant	0.5	0.25	0.025	
14	Inside Diameter 1/4"	50'	CostD32ADMIN		
15	3/8"	50'			
16	1/2"	50'			
17	5/8"	50'			
18	3/4"	50'			
19	Side Grinder- Grinding Wheel for Grinding and Blending Aluminum and Stainless Steel, Max RPM 13,300, Comply with ANSI B7.1 4 1/2" x 3/16" x 7/8" Raised D32ADMIN Arbor				
20	Side Grinder- Stainless Steel grinding wheel for grinding stainless steel, Max RPMs 13,300, Comply with ANSI B7.1 4 1/2" x (5/64-1/25) 7/8" Flat Arbor				
21	Die Grinder-Cut off wheel for Aluminum and Non Ferrous Metals, RPM 25,000, Comply with ANSI B7.1 3" x 1/32" x 3/8" Arbor Hole Flat				

Item #	Description				Unit Price
22	Drill Bit Set, 29 pieces, 1/16" to 1/2" in 64ths, Hardness (core/surface) 64RC/88RC, Heat Resistant (core/surface) 1,100 degree F and 1450 degree F, NCM-8 chrome moly vanadium, High Speed Tool Steel, Heat Treatment Austempered Twice				
23	Drill Bit Set, 29 pieces, 1/16" to 1/2" in 64ths, CM-88 chrome moly cobalt high heat steel, Aircraft specs meet NAS 907 Type J, Heat Resistant 1,200, Hardness 66-68 RC, Tip design 135 degrees split point Phillips Pan Head Machine Screws, 18-8 Stainless Steel, 18-8 chrome/nickel stainless steel, approval meet ANSI/ASME B18.6.3				
24	1/4" - 20 x 1/2"				
25	1/4" - 20 x 3/4"				
26	1/4" - 20 x 1"				
27	1/4" - 20 x 1 1/4"				
28	1/4" - 20 x 1 1/2"				
29	1/4" - 20 x 2"				
	Primary Wire, 100% electrolytic copper, Insulation - PVC, Voltage Automotive and Marine 12-24 V, temp range 20 degree F to 250 degree F, SAE type GPT				
	Color	Gauge	Roll		
	Black	14	100'		
	Red	14	100'		
	White	14	100'		
	Black	12	100'		
	Red	12	100'		
	Fuses				
	ATO Type	Qty per Box			
30	Red 10amp	5			

Item #	Description		Unit Price
31	Light Blue 15amp	5	
32	Yellow 20amp	5	
33	Green 30amp	5	
	Mini Fuses		
34	Red 10amp	5	
35	Blue 15amp	5	
36	Yellow 20amp	5	
	Maxi Fuses		
37	Green 30amp	1	
38	Red 50amp	1	
39	Blue 60amp	1	

Parts List from Fleet Maintenance Department			
Item #	Description	Unit Price	
40	1/4"-28 Nut		
41	5/8"-24 Nut		
42	3/8"-24 Nut		
43	7/16"-20 Nut		
44	1/2"-20 Nut		
45	1/4"-28 x 1/2" Bolt		
46	1/4"-28 x 1 Bolt		
47	1/2"-28 x 1 1/2" Bolt		
48	1/4"-28 x 2" Bolt		
49	1/4"-28 x 2 1/2" Bolt		
50	1/4"-28 x 3" Bolt		
51	5/16"-24 x 1/2" Bolt		
52	5/16"-24 x 3/4" Bolt		
53	5/16"-24 x 1" Bolt		
54	5/16"-24 x 1 1/2" Bolt		
55	1/4" Washer SAE		
56	5/16" Washer SAE		
57	3/8" Washer SAE		

Item #	Description	Unit Price
58	7/16" Washer SAE	
59	1/2" Washer SAE	
60	5/8" Washer SAE	
61	7/8" Lock Washer	
62	7/8" USS Flat Washer	
63	7/16"-14 Hex Nut	
64	1/2"- 13 Hex Nut	
65	9/16"-12 Hex Nut	
66	1/8" Brass Pipe	
67	1/4" Brass Pipe	
68	3/8" Brass Pipe	
69	1/2" Brass Pipe	
70	1/8" Pipe Coupling	
71	3/8" Pipe Coupling	
72	1/4" Pipe Coupling	
73	3/4" Pipe Coupling	
74	1/2" Cable Clamp	
75	5/16" Cable Clamp	
76	7/16" Cable Clamp	
77	3/4" Cable Clamp	
78	9/16" Cable Clamp	
79	1/4" Cable Clamp	
80	1/4" Quick Chain Link	
81	3/16" Quick Chain Link	